## **Model CONFORM SE**



#### Description

Exclusive velour, recycled ECONYL yarn, tailored to suit appearance of wood and designer floors, low-flammability version: fire classification Cfl-s1







Castor-resis-



Suitable for stairs



DS (EN 13893)



Resistant strength



Cfl-s1





Luxurious



Highly suitable for property



# **Model CONFORM SE**

Construction	Tufting-Velours 1/8"
	3
Pile above substrate	100% polyamide ECONYL
Substrate material	Polyester fleece
Backing material	Synthetic latex
Pile weight / fibre weight	1.200
Total weight (g/m²)	2.400
Overall height (mm)	8,5
Tuft density/m <sup>2</sup>	132.280
Slip resistance	DS (EN 13893)
Certificates	CE conformity EN 14041 (rolls only)
Supplied as rolls SE/ Bfl-s1	400 cm wide (no border)
Product characteristics	Soiling and moisture absorption
Laying	Individual rolls or smaller coverings can be laid loose on any smooth floor. For larger areas, and allowing for on-site conditions, we recommend fixed laying with an adhesive suitable for plasticised PVC.

Cleaning	Dirt removal with powerful brush vacuum cleaner. The spray extraction process is recommended for periodic basic cleaning. Cleaning with plenty of water is absolutely no problem, water temperature should not be above 40°C. Do not use chlorinated hydrocarbon (Tetra).
Brand	emco

Suitable for:
Residential and care homes
Arena
medical practice
Train station
Offices and administrative buildings
Family home
University / Higher education institution
airport
Hotel
Kindergarten/Nursery
Apartment building
Trade fair
School
Sports hall



## **Model CONFORM SE**


### Colours







Mocha 76.03



76.02 Beige



76.04 Brown

